


RB ROAD BLOCKER TECHNICAL SPECIFICATIONS



RB		Number of Pistons	H = 60 cm	H = 90 cm
X	L x W x D (mm)		L x W x D (mm)	
1,0 mt	BLOCKER CABINET	Single	1275 x 1170 x 975	1680 x 1170 x 1270
1,5 mt		Single	1275 x 1670 x 975	1680 x 1670 x 1270
2,0 mt		Single	1275 x 2170x 975	1680 x 2170x 1270
2,5 mt		Single	1275 x 2670 x 975	1680 x 2670 x 1270
3,0 mt		Single	1275 x 3170 x 975	1680 x 3170 x 1270
3,5 mt		Optional	1275 x 3670 x 975	1680 x 3670 x 1270
4,0 mt		Optional	1275 x 4170 x 975	1680 x 4170 x 1270
4,5 mt		Double	1275 x 4670 x 975	1680 x 4670 x 1270
5,0 mt		Double	1275 x 5170 x 975	1680 x 5170 x 1270
5,5 mt		Double	1275 x 5670 x 975	1680 x 5670 x 1270
6,0 mt		Double	1275 x 6170 x 975	1680 x 6170 x 1270
6,5 mt		Double	1275 x 6670 x 975	1680 x 6670 x 1270

*Dimensions are approximate and subject to change according to cabinet top lid dimension variation.

- Power** : Standard 380V 3-Phase 50/60 Hz, 3,3 - 5,5 KvA motor (varies depending on blocker size).
Opt. 220V, 110V 1-Phase 50/60 Hz; or 24V DC (for some models/sizes only).
- Control Pack** : 24V DC powered and PLC control unit is placed in power unit cabinet. -
Solenoids 24V DC (Ops.12V DC / 220V AC)
- Speed** : Standard Operation ~4 - 6 sec. (ascend/descend) (opt. 2,5 - 4 sec.) depending on unit dimensions. Emergency raise up (upwards) by optional hydraulic accumulator ~1,5 sec. and may vary depending on unit dimensions.
- IP Rating** : IP 55 - Hydraulic Power Unit,
IP 58 - Blocker Cabinet (underground unit),
IP 67 - Electronics (optional), protection with housing/box,
IP 68 - Hydraulic Piston
- Crash / Impact Rating** : Designed and produced to withstand M40 P1 (K-8).
- Axle Load Resistance** : 40T
- Hydraulic Cylinder Unit** : Heavy duty, electrostatic powder coated, dust sealed hydraulic cylinder.
Models between 1- 4 meter widths contain a single piston.
(Double piston versions are optionally available for models in 4 meter widths).
Models between 4,5 - 6,5 meter widths contain double pistons.
Cylinder unit features a safety valve against leakage and hose failure.
- Hydraulic Power Unit** :- Strengthened industrial pump,
- 60 lt oil tank capacity with magnetic metal collector and particle filter,
- Built-in oil level and temperature indicator,
- 70-80 Bar pressure; maximum running pressure is 120 Bar
- 10 mt R2 (double wire braided mesh) reinforced hydraulic hose.
- System** : Down, Up, Emergency and external sensor inputs/outputs (e.g. Loop Detector, Beam Detector, Signalization, Remote Control, etc.).
System alerts with an audio signal during lowering and raising operation.
A loud siren output in case of alarm or emergency.
Can be lowered or raised automatically in case of emergency (User's preference).
Can be lowered and raised manually in case of power failure or during the maintenance service with manual pump and manual valve feature.

Automatic raise up mode deploys (optionally with synchronized loop detector) the road blocker after the vehicle has passed over.
Sensor controlled stopping both at the top and bottom positions of the blocker unit.

Power Unit : Motor, hydraulic pump and solenoid valves are contained in an easily accessible hot-dip-galvanized and electrostatic powder painted cabinet with a built-in lock lid. (Opt. Stainless Steel Cabinet)
Cabinet Dimensions: 1000x570x1200mm (WxLxH)

Blocker Cabinet (underground unit) : All parts are colored with industrial paint with two components.
U-shaped profile structure for maximum strength.
The blocker and cabinet are designed so that no vehicle crashing effect can displace it after embedded or installed in to the ground.

Blocker Unit (impact blocking unit) : All parts are colored with industrial paint with two components.
Hot dip galvanised vehicle pass through surface (top plates).
The construction is aesthetically and functionally completed with reflecting strips and warning signs.
The hinge system is specially designed to have a flattened surface level with the top plate so that vehicles can pass over smoothly and quietly.
Top panel where the vehicle pass over is made of 8/9mm thick non-slip surface steel hot dip galvanised before paint.
The system moves up and down with 50mm diameter stainless steel hinges (example: 3 meter blocker contains 7 pieces of 50mm diameter stainless steel hinges).
Blocker unit raises 45° angle from the ground level and can be equipped with equipped with optional flashing light indicators on side and front panels.
A top lid is provided for easy access for service and maintenance on the top plate.

Control System : **Manual Control Button Unit:**
Provided with an IP67 CRM yellow box including 3 switches for downwards, upwards, stop (optional emergency operation), can stop the block motion with the command/signal coming from detector, equipped with built-in LED visual indications and 10mt cable.

Compatibility with Access Control Systems:
Can be utilized through, card reader, finger print, biometric systems and similar any kind of access control systems (by third parties)¹

Optional Unit
With the optional model "RB CONT.UNIT.V.001" users can monitor the diagnostic functions, can be accessed through LAN, RS485 protocols. System is provided inside a metal cabinet that also includes the other functional switches like downward, upward, stop, emergency operations.
With the built in 124x68 LCD screen, all status of the operation and system diagnostic can be monitored through messaging functions like oil status, loop or beam detectors status, water level inside the cabinet, blocker position according to user preference, any .bmp files can be displayed.
The system is driven by the PLC.

Optional Features and Accessories : Traffic lights (red-green), Traffic light Pole, Loop Detector (double/single contact), Beam Detector, 220V or 24V DC motor, Remote Control (receiver and transmitter are 3 channels), UPS, Photocell Sensor (receiver+ transmitter with 50cm height pole), RB CONT. UNIT.V.001 Control Unit, Intercom, External Buttons, Emergency Submersible Pump (9000 lt/h or 18000 It/h), Hydraulic Accumulator for emergency fast raise up (1 piston or 2 pistons systems), Surface Frame (sizes: from 250mm to 1000mm), Oil Cooler, Oil Heater, Heater for electronic components, hot-dip galvanization for cabinet, blocker and impact facing surface units, double effect hydraulic unit, double speed hydraulic unit, ground mounting plate, powered audio signal (siren), PLC diagnostic monitor, flashing light indicators, round shaped front panel, oil level sensor, optional speed, IP67 box (for PLC, SMPS, connectors etc inside power unit).

Installation : Easy Installation with C30 Grade Concrete